

## Hybrid Neural Network-Genetic Algorithm Framework for EEG and ECG Signal Classification

Hussain Ali Mutar, Shaima Miqdad Mohamed Najeeb, Mohand Lokman Aldabag and Haider TH Salim ALRikabi

DOI: 10.53759/7669/jmc202606021


Reference: JMC202606021

Journal: Journal of Machine and Computing

Received On: 18 May 2025

Revised On: 22 August 2025

Accepted On: 01 October 2025



**Please cite this article as:** Hussain Ali Mutar, Shaima Miqdad Mohamed Najeeb, Mohand Lokman Aldabag and Haider TH Salim ALRikabi, “Hybrid Neural Network-Genetic Algorithm Framework for EEG and ECG Signal Classification”, Journal of Machine and Computing. (2026). Doi: <https://doi.org/10.53759/7669/jmc202606021>.

This PDF file contains an article that has undergone certain improvements after acceptance. These enhancements include the addition of a cover page, metadata, and formatting changes aimed at enhancing readability. However, it is important to note that this version is not considered the final authoritative version of the article.

Prior to its official publication, this version will undergo further stages of refinement, such as copyediting, typesetting, and comprehensive review. These processes are implemented to ensure the article's final form is of the highest quality. The purpose of sharing this version is to offer early visibility of the article's content to readers.

Please be aware that throughout the production process, it is possible that errors or discrepancies may be identified, which could impact the content. Additionally, all legal disclaimers applicable to the journal remain in effect.

© 2026 Published by AnaPub Publications.

# Hybrid Neural Network-Genetic Algorithm Framework for EEG and ECG Signal Classification

Hussain Ali Mutar<sup>1</sup>, Shaima Miqdad Mohamed Najeeb<sup>2</sup>, Mohand Lokman Aldabag<sup>2</sup>, Haider TH. Salim ALRikabi<sup>3</sup>

<sup>1</sup>College of Computer Science and Information Technology, Wasit University, Wasit, Iraq, Email: [hmutar@uowasit.edu.iq](mailto:hmutar@uowasit.edu.iq)

<sup>2</sup> Department of Cyber Security and Cloud Computing Techniques Engineering, Northern Technical University, Mosul, Iraq, Email: [shaimaamqdad76@ntu.edu.iq](mailto:shaimaamqdad76@ntu.edu.iq)

<sup>3</sup> Electrical Engineering Department, College of Engineering, Wasit University, Wasit, Iraq, Email:

<sup>4</sup>[hdhiyab@uowasit.edu.iq](mailto:hdhiyab@uowasit.edu.iq)

## Abstract:

Digital signal processing (DSP) techniques are pivotal in extracting clinically relevant information from biomedical signals such as electroencephalogram (EEG) and electrocardiogram (ECG). This paper introduces a hybrid framework that synergizes Convolutional Neural Networks (CNNs) with Genetic Algorithms (GAs) to enhance the classification accuracy of EEG seizures and ECG arrhythmias. The methodology employs wavelet transforms for noise-robust feature extraction and a GA for automated hyperparameter optimization of a CNN-BiLSTM architecture. Evaluated on the CHB-MIT EEG dataset (23 subjects) and MIT-BIH ECG dataset (47 subjects), the proposed model achieves 96.3% and 95.8% accuracy, respectively, outperforming ResNet-18 and SVM baselines. Statistical tests (Wilcoxon signed-rank,  $p < 0.01$ ) confirm the significance of improvements. The optimized model reduces inference latency by 38% and is suitable for edge deployment in real-time diagnostic systems.

**Keywords:** Digital Signal Processing, Neural Networks, Genetic Algorithms, EEG, ECG, AI.

## 1. Introduction

Digital Signal Processing (DSP) was fundamentally uprisng the medical diagnostics fields by providing the computational tools essentials to interpret complex, non-stationary biological signals. [1]. Among these, electroencephalogram (EEG) and electrocardiogram (ECG) signals represent as two of the most important and frequently used types for evaluating neurological and cardiovascular health, respectively. EEG captures the brain's electrical activity, provides insight into neurological states like epilepsy, trouble sleeping, and mental functions. on the other hand, ECG captures the heart's electrical impulses, is the main diagnostic tool for diagnosing arrhythmias, ischemic heart disease, and other serious cardiac disorders. The clinical utility of these signals. However, inherent difficulties such as low signal-to-noise ratios, biological noise, and significant inter-patient variability commonly reduce the clinical utility of these signals [2].

For many years, traditional DSP methods, like Fourier transforms and Kalman filtering, have served as the backbone of biomedical signal analysis for decades. For example, the Fourier transform performs adequately when detecting periodic components in stationary signals but fails when examining non-stationary signals, such as EEG and ECG, where the frequency content changes over time. To address this, time-frequency representations such as Short-Time Fourier Transform (STFT) were developed, but they suffer from a fixed resolution trade-off, limiting their ability to precisely localize transient events such as epileptic spikes or premature ventricular contractions. These limitations of conventional methods have created a pressing need for more sophisticated, adaptive analytical frameworks [3].

A major paradigm shift occurred with the rise of machine learning (ML), which replaced manual feature extraction with automatic pattern recognition. In order to classify EEG and ECG signals using engineered features derived from wavelet transforms, entropy measures, or statistical properties, supervised learning models—in particular, Support Vector Machines (SVMs)—have been widely used. These methods are naturally constrained by the caliber and applicability of the manually chosen features, which necessitates a high level of domain expertise and is

frequently not transferable to other datasets or patient populations, even though they can attain reasonable accuracy [4].

Deep learning (DL), as a subfield of ML, has been a popular substitute, as it automatically learns hierarchical features directly from raw, minimally processed data. Convolutional Neural Networks (CNNs) have been incredibly successful in image-based medical diagnostic work and have been directly adapted with great effectiveness for analysis of 1D signals and 2D time-frequency domains[5]. Recurrent Neural Networks (RNNs) are specifically ideal for sequential data such as EEG and ECG because of the long-range temporal dependencies that are modeled by it. Deep residual learning-based models like ResNet-18 have raised the bar for classification tasks, but frequently at the expense of high computational complexity and a large number of parameters that need careful tuning.

Despite their promise, deep learning models introduce their own set of challenges. The performance of these models is highly sensitive to their hyperparameters, including the number of layers, learning rate, and dropout rate. The process of optimizing these parameters is typically manual, relying on grid or random search, which is not only computationally expensive and time-consuming but also often leads to suboptimal configurations. Furthermore, pure deep learning approaches can act as "black boxes," offering limited interpretability and struggling to generalize in the presence of noisy, heterogeneous clinical data acquired from diverse sources with varying protocols [6].

This gap between the potential of deep learning and its practical clinical application underscores the necessity for a more robust and intelligent framework. There is a clear need for systems that not only achieve high accuracy but also optimize their own architecture for efficiency and generalizability. This is where evolutionary algorithms, particularly Genetic Algorithms (GAs), present a compelling solution. GAs, inspired by natural selection, can efficiently navigate vast and complex hyperparameter spaces to find near-optimal solutions, thereby automating the tuning process that is otherwise a major bottleneck [7].

Therefore, the primary issue that this work solves is the creation of an integrated, intelligent system that combines the best of advanced DSP for noise-resistant feature extraction, the pattern discrimination ability of deep neural networks, and the optimization efficiency of genetic algorithms. This is a hybrid system that tries to transcend the shortcomings of past systems by mechanizing the most difficult parts of model construction and tuning.

The work in the paper presents an original hybrid Neural Network-Genetic Algorithm (NN-GA) framework entirely for the classification of EEG and ECG signals. The proposed framework integrates a wavelet-based preprocessing stage to enable advanced time–frequency analysis, followed by a hybrid CNN–BiLSTM architecture that concurrently captures both spatial and temporal feature representations. To enhance model adaptability and ensure optimal performance, a genetic algorithm (GA) is employed for the automated tuning and optimization of critical hyperparameters.

. All of these are integrated in such a manner as to improve accuracy, robustness, and computational efficiency all at the same time.

This paper is structured as follows: Section 2 presents a critical survey of the literature with an exposition of the identified research gaps. Section 3 details the planned methodology, including the system architecture, signal processing workflows, and genetic algorithm optimization process. Section 4 details the framework of implementation and ensuing outcomes, followed by an elaborate discussion in Section 5. Finally, the conclusion summarizes the outcomes and suggests future research possibilities.

## **2. Critical Analysis & Literature Review**

The landscape of biomedical signal classification is richly populated with diverse methodologies, each with distinct strengths and weaknesses. A critical analysis of these approaches is essential to contextualize the contributions

of this work. The existing literature can be broadly categorized into traditional DSP-based methods, machine learning models with handcrafted features, and deep learning approaches.[8].

**Traditional DSP Techniques:** The foundation of signal analysis was built upon transformative mathematical tools. The Fourier Transform, while revolutionary, assumes signal stationarity, a condition rarely met by biological signals. The advent of the Short-Time Fourier Transform (STFT) introduced a time-varying perspective but was hamstrung by the Heisenberg uncertainty principle, forcing a fixed resolution trade-off across all frequencies [9]. This is particularly problematic for analyzing ECG arrhythmias or EEG seizures, where both high-frequency transients and low-frequency oscillations carry critical diagnostic information. Wavelet Transform emerged as a superior alternative, offering multi-resolution analysis that adapts to signal characteristics. Studies have consistently shown that wavelets like Daubechies (db4) and Morlet are highly effective in isolating pathological features from noise. However, a significant limitation persists: these methods merely transform the data. The subsequent step of feature selection—choosing which wavelet coefficients or statistical measures (energy, entropy, variance) to use—remains a manual, expert-driven process that is prone to bias and lacks scalability[10].

**Machine Learning with Engineered Features:** This paradigm combines DSP for feature extraction with classifiers like Support Vector Machines (SVMs), k-Nearest Neighbors (k-NN), and Random Forests. Ullah et al. (2020) exemplified this approach, achieving 88.2% accuracy in EEG seizure detection by feeding SVM with features from wavelet decomposition [8]. Similarly, numerous studies on ECG classification have used SVMs with features from QRS complex morphology and RR interval variability [11]. One of the key advantages of this paradigm lies in its interpretability, as the features employed for classification are explicitly defined and easily understood. Nevertheless, a significant limitation is the considerable burden associated with feature engineering. The overall performance of the model is heavily influenced by the discriminative capacity of manually selected features. This approach is not only resource-intensive and reliant on substantial domain expertise, but it also risks overlooking critical information. Consequently, the resulting models may be suboptimal and exhibit limited generalization capability when confronted with novel data originating from different populations or acquisition devices.

>Deep Learning Methods: Deep learning bypassed the bottleneck of feature engineering and learned the features directly from data. CNNs applied on 2D spectrograms or scalograms of EEG/ECG signals have been proven very successful. Rajpurkar et al. (2019) established the potential for CNNs by reporting cardiologist-level detection of arrhythmias from raw ECG traces [12]. In the case of sequential data, LSTMs and Gated Recurrent Units (GRUs) have been used to capture temporal dynamics. Singh et al. (2023) applied LSTM networks for the analysis of ECG signals, detecting long-range dependencies inside heartbeats[13]. More recently, multimodal fusion models such as CNN-LSTM have become popular as a means of taking advantage of both spatial feature learning and sequential modeling. For example, CNNs have been used to learn features on very small segments of signals and LSTMs used for modeling the sequence of what are learned features, with better performances over unimodal models reported [14].

**Hyperparameter Tuning Problem:** A universal and core challenge in the area of deep learning applications is hyperparameter optimization. The efficiency of a CNN-LSTM model is very sensitive to selections such as the number of convolutional filters, the size of the kernel, the number of LSTM cells, the learning rate, and the probability of dropout. The older methods of manual tuning or the grid search are computer-intensive, particularly with large datasets and large model sizes as are often encountered in medical informatics. For instance, the training time of a single configuration of a deep learning model on a large dataset might run over hours or even days, rendering an exhaustive search of a multi-dimensional parameter space practically infeasible. Due to the

above situation, unfortunately, researchers end up with sub-optimal configurations with much potential gain in performance left untapped [15].

**Evolutionary Algorithms in Medicine:** Evolutionary algorithms, and Genetic Algorithms (GAs) in particular, are an effective metaheuristic technique for solving this optimization problem. Based on Darwinian concepts of natural selection, GAs hold a population of candidate solutions (hyperparameter-encoded chromosomes) that are updated over subsequent generations according to selection, crossover, and mutation operations. Because of their effectiveness in searching through a large non-differentiable space, they are of especial value for neural architecture search (NAS) and hyperparameter optimization [16]. GAs have been used with immense success in several medical fields, such as medical image segmentation with optimized networks and feature selection with genomic data. Using GAs in the processing of EEG/ECG is the next logical step; however, an integrated framework with a combination of wavelet-DSP and a CNN-BiLSTM learner and GA optimization is yet to be thoroughly researched [16].

**Bidirectional LSTMs and Clinical Interpretability:** LSTMs model time sequences but process inputs in one direction (i.e., forward). BiLSTMs process inputs in both forward and backward ways such that the network apprehends contextual cues from future and previous states equally. It is especially useful for medical signals, for which the context of an event (i.e., what is happening before and after an epileptic spike) is very important for the model's clear categorization. In addition, clinical implementation of AI models is not only based on accuracy but also on trustworthiness and interpretability. Methods such as SHAP (SHapley Additive exPlanations) and attention mechanisms are increasingly being incorporated so as to emphasize what regions of the signal best impacted on the decision of the model, departing from the "black box" perception [17].

**Recognized Gaps in Existing Research:** In conducting this extensive analysis, three major gaps have been identified. First, there is a lack of automated optimization of architecture. The top modern models remain heavily reliant on labor-intensive, intuition-driven tuning of hyperparameters as is ultimately inefficient and suboptimal. Second, there are myriad models with difficulty with robustness of features. No matter what learned features are used in some models, there is no guarantee that they are optimally robust against the significant noise and variability typical of clinical data at large. Hard-coded transformations, such as FFT or STFT, used in past methodologies are inherently undesirable for processing non-stationary signals. Third, there is a major gap with regard to clinical scalability and validation. Various postulated models are validated on sparse, homogenous sets of data or are subject-specific in training and consequently are not available for wider, multi-center populations with differing recording protocols and demographic profiles.

**Bridging the Gaps:** The present study seeks to concurrently address these disparities through an innovative integrated framework. It introduces an automated architecture search utilizing a Genetic Algorithm (GA) to obviate the necessity for manual tuning, incorporates a wavelet-CNN fusion step to guarantee reliable, multi-resolution feature extraction that is inherently appropriate for non-stationary signals, and engages in thorough clinical validation utilizing extensive, standardized, publicly accessible databases (CHB-MIT and MIT-BIH) encompassing over 23,000 samples to affirm scalability and generalizability. This triadic approach is formulated to establish a system that not only achieves high accuracy but also demonstrates efficiency, robustness, and clinical relevance.

### **3. Relevant Literature**

The quest for precise automated diagnosis with the application of EEG and ECG signals resulted in an enormous amount of corresponding research, and it is analyzed with the prisms of signal processing, model structure, and optimization methods.

**Signal Processing for Feature Extraction:** The existing literature on feature extraction is predominantly characterized by methodologies associated with time-frequency analysis. Before the advent of deep learning, the discipline significantly depended on the extraction of manually crafted features derived from transformations such as Wavelet Packet Decomposition (WPD) and Empirical Mode Decomposition (EMD). For instance, several

investigations have employed WPD to disaggregate EEG signals into sub-bands, subsequently computing metrics such as energy, entropy, and standard deviation from these sub-bands to be utilized in classifiers like Support Vector Machines (SVM) [18]. EMD, which adaptively segments a signal into Intrinsic Mode Functions (IMFs), has similarly been utilized for the purpose of ECG noise reduction and feature extraction. Although effective, these techniques essentially redirect the challenge from the analysis of raw signals to the evaluation and selection of appropriate features within the transformed domain, a process that still necessitates expert involvement. Our research builds upon the advantages of wavelet techniques—specifically through the application of the Continuous Wavelet Transform (CWT) to produce scalograms; however, we significantly reinterpret these scalograms as image inputs for a Convolutional Neural Network (CNN), enabling the network to autonomously identify the most distinguishing features from this comprehensive time-frequency representation, thereby streamlining the final and most pivotal phase of feature selection.

**Deep Architectures for EEG/ECG:** A major body of corresponding work was dedicated to innovating model structures. Direct application of CNNs on 1D sequences of signals or, and more frequently, on 2D transformed representations such as spectrograms and scalograms was typical. Acharya et al. (2017) applied a 9-layered CNN on segments of ECGs for detecting arrhythmias and showcasing the effectiveness of automated feature learning [19]. In the case of EEGs, Bashivan et al. (2015) applied CNNs on spectral power maps for recognizing cognitive load. In an attempt to retain temporal context, the application of RNNs followed. Singh et al. (2023) experimented with LSTM networks for sequences modeling of ECG beats. The logical next step was an integration of the best of both and hence followed the development of CNN-RNN hybrids. For example, a typical framework employs a CNN front-end for extracting features and an RNN back-end (LSTM/GRU) for modeling sequential time.

This paper suggested CNN-BiLSTM falls into the same group but improves upon it with the deployment of LSTM layers in a bidirectional fashion, enjoying an advanced contextual understanding of the signal with an analysis in forward and backward orders, a detail usually lacking in earlier work.

**Optimization and Hyperparameter Tuning:** The optimization techniques discussed in earlier work are usually simplistic. A large number of studies resort to manual tuning or simplistic grid/random search techniques, which are resource-intensive and inefficient in the high-dimensional settings [20]. There are recent studies that begin exploring Bayesian optimization for tuning hyperparameters, building a probabilistic model that captures the mapping between hyperparameters and validation performance. However, Bayesian optimization is susceptible to sensitivity of its own prior distributions and may struggle as it handles categorical parameters. Genetic Algorithms (GAs) offer a robust global search mechanism with decreased sensitivity to initial conditions and are capable of handling a wide range of parameter types such as continuous, integer and categorical variables. While GAs have been used in the past independently for selection of informative features or tuning of simple classifiers, application of GAs for end-to-end hyperparameter optimization of an elaborate hybrid CNN-BiLSTM model for biomedical signals, as we propose, is a valuable extension. Our GA is specially designed with a fitness function aligned with clinical goals with an order of preference for sensitivity and specificity over accurate prediction.

**Hybrid Intelligent Systems:** The notion of hybridizing one computational intelligence paradigm with another is an increasing trend. There is work combining fuzzy logic with neural networks or SVMs with GAs for selecting the best sets of features. For instance, there are researchers who have employed GAs for selecting the best possible subset of features from an extensive set of manually created features prior to classification. What is unique about our work is the degree of integration. [21]. Table 1 shows a comparative analysis of medical DSP approaches.

Table 1: Comparative Analysis of Medical DSP Approaches

| Study                        | Method   | Accuracy | Limitations                  |
|------------------------------|----------|----------|------------------------------|
| Rajpurkar et al. (2022) [22] | CNN-ECG  | 94.00%   | Manual hyperparameter tuning |
| Ullah et al. (2020) [23]     | SVM-EEG  | 88.20%   | Feature engineering overhead |
| Singh (2023) [24]            | LSTM-ECG | 91.50%   | High computational latency   |

|               |               |        |      |
|---------------|---------------|--------|------|
| Proposed Work | CNN-BiLSTM/GA | 96.30% | None |
|---------------|---------------|--------|------|

Hybrid Intelligent Systems: The concept of hybridizing different computational intelligence paradigms is a growing trend. There is related work on combining fuzzy logic with neural networks or SVMs with GAs for feature selection. For example, some researchers have used GAs to select the optimal subset of features from a large pool of handcrafted features before classification. However, this work is distinct in its level of integration.

This study applies hybridization at three levels: wavelet-based signal processing, a CNN–BiLSTM model, and GA-driven optimization. Together, they form a closed-loop system in which the GA refines the architecture learning from wavelet-transformed signals, achieving a balanced and synergistic design rarely addressed in existing studies. For evaluation, the MIT-BIH Arrhythmia and CHB-MIT Scalp EEG databases are employed as standard benchmarks, ensuring fair comparison with state-of-the-art methods. Reported gains in accuracy, F1-score, and efficiency are thus grounded in a rigorous and widely recognized framework.


### 3. Methodology

Research methodology was defined as an integrated, multi-step framework for tackling the deeper issues regarding biomedical signal classification, namely robustness against noise, concise feature selection, spatiotemporal modeling, and auto-optimization. The methodology approach combines up-to-date digital signal processing (DSP) techniques with a hybrid deep learning framework, with automatically optimized and not manually optimized parameters. The resulting model is thus not only accurate but efficient and transferable as well. The entire process, from raw input signal to classified output, is rendered reproducible and consistent with clinical diagnostic practice, with robust cross-validation techniques for overfitting prevention and statistical significance. The subsequent sections elaborate upon each detail of this complex framework.

#### 3.1 Architectural Framework

The system architecture, depicted in Figure 1, is a closed-loop, modular framework consisting of four interconnected core modules that work in sequence to transform raw, noisy physiological signals into accurate clinical classifications. The modular design is a critical strength, allowing for individual components (e.g., the type of wavelet transform or the classifier itself) to be upgraded or replaced without necessitating a complete redesign of the entire system, thus ensuring longevity and adaptability to future technological advancements. The pipeline begins with the Preprocessing Module, which is responsible for cleansing the raw EEG and ECG signals of various artifacts and noise, preparing a clean signal for subsequent feature extraction.

This cleansed signal then flows into the Feature Extraction Module, where the Continuous Wavelet Transform (CWT) is applied to generate a time-frequency representation (scalogram) of the signal. This step is crucial for converting the 1D temporal signal into a 2D image that encapsulates both when and at what frequency events occur, providing a rich feature set for the neural network. The resulting scalogram is fed into the Classification Module, a hybrid CNN-BiLSTM network that serves as the intellectual core of the system. The CNN layers extract hierarchical spatial features from the scalogram, while the BiLSTM layers model the temporal dynamics and contextual relationships within these features. The output of this module is a preliminary classification.



overseen and refined by the Optimization Module, which employs a Genetic Algorithm (GA). The GA operates on a meta-level, using the classification performance (e.g., accuracy, sensitivity) as a fitness score to evaluate different sets of hyperparameters for the CNN-BiLSTM model. This creates a feedback loop where high-performing configurations are genetically combined and mutated over generations, automatically guiding the system towards an optimally tuned model. This closed-loop design enables continuous improvement and is key to achieving the high performance and efficiency reported in the results.

### 3.2 Signal Preprocessing

Signal preprocessing is a necessary and worthwhile preliminary step in dealing with EEG and ECG signals as the raw signals are inevitably corrupted by noise that could significantly impair classification effectiveness. This noise originates from a variety of sources (e.g., physiological artifacts of muscle activity, eye movements or eye blinks, respiration), powerline interference, and contact noise of electrodes. The general aim of this step is to raise the signal-to-noise ratio (SNR) to a favorable level by eliminating such artifacts without losing useful pathological patterns that will assist in medical diagnostics. To this end, special processing pipelines have been tailored to those of EEG and ECG signals given their own physiological sources and noisy nature, which can be divided to:

#### 3.2.1 EEG Processing Pipeline

The EEG processing pipeline is meticulously designed to isolate cerebral activity from pervasive contaminants. The first step involves Bandpass Filtering using a Chebyshev Type II filter (0.5-40 Hz). This specific filter was chosen for its sharp roll-off and stopband attenuation, effectively eliminating low-frequency drift caused by perspiration or respiration and high-frequency electromyographic (EMG) noise from scalp and jaw muscles. The mathematical representation of the filter transfer function:

$$H(z) = \frac{\sum_{k=0}^M b_k z^{-k}}{1 + \sum_{k=1}^N a_k z^{-k}}$$

illustrates the algorithmic removal of these unwanted frequency components. Following filtering, Artifact Removal is performed using Independent Component Analysis (ICA).

ICA is a powerful blind source separation technique that decomposes the multi-channel EEG signal into statistically independent components. Components corresponding to stereotypical artifacts like ocular blinks (slow, high-amplitude) and muscle activity (high-frequency) are visually identified and manually rejected before the signal is reconstructed, significantly cleansing the data. Finally, Normalization via min-max scaling is applied to constrain the amplitude of all channels to a common range of  $[-1, 1]$ . This step ensures that the learning algorithm is not biased by the arbitrary amplitude scales of different subjects or recording sessions, promoting faster convergence and stable model training.

#### 3.2.2 ECG Processing Pipeline

The ECG processing pipeline addresses challenges specific to cardiac signals, primarily baseline wander and high-frequency noise. Baseline Correction is achieved using an adaptive Least Mean Squares (LMS) filter with a step size ( $\mu$ ) of 0.01. The LMS filter adaptively estimates and subtracts the slowly drifting baseline, which is often caused by patient movement or respiration, without distorting the sharper QRS complexes that are vital for diagnosis. Subsequently, Powerline Noise Removal is performed using a 50/60 Hz notch filter with a high Q-factor of 30. This creates a very narrow stopband that aggressively attenuates the precise frequency of the powerline interference while leaving the adjacent ECG frequencies, which contain critical diagnostic information, largely unaffected.

The final stage of ECG preprocessing involves R-peak detection using the Pan-Tompkins algorithm, which combines filtering, differentiation, squaring, and integration to reliably identify QRS complexes even under noise. Accurate R-peak localization enables segmentation of the ECG into individual heartbeats, producing standardized and aligned samples that ensure consistent inputs for arrhythmia classification.

### 3.3 Wavelet Feature Extraction

The feature extraction stage moves beyond cleaned signals to transform them into a domain that maximally reveals pathological features. For non-stationary signals like EEG and ECG, the Continuous Wavelet Transform (CWT) is vastly superior to traditional Fourier-based methods because it provides optimal resolution in both time and frequency domains. The CWT, mathematically defined as:

$$\text{CWT}(a, b) = \frac{1}{\sqrt{|a|}} \int_{-\infty}^{\infty} x(t) \psi^* \left( \frac{t-b}{a} \right) dt$$

convolves the scaled and translated mother wavelets with the signal. This gives us a scalogram, an image in 2D where time is plotted along the x-axis and scale, inversely proportional to frequency, is along the y-axis, and color strength is indicative of coefficient magnitude. It essentially plots out the time-frequency-energy distribution of the signal.

Selection of the mother wavelet was of essential importance and was empirically chosen; the Daubechies-4 (db4) wavelet was chosen since it represented an optimum tradeoff between smoothness and compact support and was therefore ideally suited for the identification of the sharp, transient features that are typical of the epileptic spikes in EEG and ectopics in ECG. Scales between scale 1 and scale 128 were logarithmically distributed so as to span bands of frequency that are of physiological relevance for both classes of signals. For each processed segment, a scalogram was calculated and then divided up into defined bands of frequency of clinical relevance, e.g. the gamma (30-80 Hz) and beta (12-30 Hz) bands that are of relevance for EEG.

Based on these wavelet coefficients, an initial analysis consisted of forming a statistical feature vector containing parameters such as mean, variance, and kurtosis calculated over the coefficients falling in each frequency band. These extracted features hold both the distribution and energy attributes of the signal over specified frequency intervals. However, the complete potential of the phase is reached if the complete scalogram image (128x128 pixels) is taken as a direct convolutional neural network input. This allows the CNN itself to automatically internalize the most discriminative spatial patterns and textures existing in the time-frequency representation, thereby removing the need for manual selection of features and taking advantage of the network ability for hierarchical feature extraction out of image-like data.

### 3.4 CNN-BiLSTM Classifier

CNN-BiLSTM classifier is the foundation of the pattern recognition system, specially designed with the motivation of capitalizing on the complementary strengths of convolutional and recurrent networks for joint spatiotemporal learning. Architecture input is the two-dimensional scalogram computed from the input of the wavelet transform. The convolutional network component is a feature extractor, processing the scalogram through multiple layers of convolutional filters (3x3 kernels) with the inclusion of batch normalization and ReLU activation. These layers sequentially build up an understanding of features, ranging from basic edges and gradients in earlier layers to advanced pathological patterns reflecting seizures/arrhythmias in later layers. Interleaved max-pooling layers (2x2) are applied for spatial dimension reduction, introducing a certain amount of translational invariance, and regulating computational complexity.

The final convolutional layer's resulting feature maps are then restructured as a stream of feature vectors and so constitute a temporally sequential input channeled into the BiDirectional Long Short-Term Memory (BiLSTM) layer:

$$\begin{aligned} \overrightarrow{h}_t &= \text{LSTM}(x_t, \overrightarrow{h}_{t-1}); \overleftarrow{h}_t \\ &= \text{LSTM}(x_t, \overleftarrow{h}_{t-1}) \end{aligned}$$

This is a critical innovation; while a standard LSTM processes sequences in one temporal direction, a BiLSTM processes the data in both forward and backward directions. This allows the network to contextualize each time

point in the scalogram not only with what came before it but also with what comes after it. For medical signals, this bidirectional context is invaluable, as the onset of an event (like an epileptic spike) can be better understood by seeing the brief suppression of activity that often follows it.

### CNN-BiLSTM Classifier Architecture

An iterative process was employed to design the classifier's specific architecture, which is shown in Figure 2, and the Genetic Algorithm subsequently improved it. A 128x128 single-channel (grayscale) scalogram is intended to be received by the input layer. 64 filters with 3x3 kernels make up the first convolutional block, which is followed by a 2x2 max-pooling layer, batch normalization, and a ReLU activation function. Low-level feature capture is the responsibility of this block. The network can learn more intricate and abstract representations from the time-frequency domain by increasing the number of filters to 128 with a second, deeper convolutional block.

After that, the second convolutional block's output is transformed from a 3D tensor into a 2D sequence that can be fed into the recurrent layers. A bidirectional LSTM layer with 128 units in each direction receives this sequence as input, producing 256 features in total. The GA ultimately optimized the trade-off between computational efficiency and model capacity, which led to the selection of 128 units. Prior to being linked to the last classification layer, the BiLSTM layer's output is regularized with a dropout rate of 0.3. For multi-class classification problems, the Adam optimizer ( $\beta_1=0.9$ ,  $\beta_2=0.999$ ) is used to optimize the entire network. It adjusts the learning rate during training, and categorical cross-entropy is used to calculate the loss.




Figure 2: 2CNN-BiLSTM Architecture Diagram

### 3.5 Genetic Algorithm Optimization

The foundation of the framework's automation is the Genetic Algorithm (GA) optimization module, which is made to effectively traverse the extensive and intricate hyperparameter search space that would be impossible to investigate by hand. A candidate solution (a unique model configuration) is represented as a chromosome in the first step of the process, known as chromosome encoding. The number of CNN layers (2–5), the number of LSTM units (32–256), the dropout rate (0.1–0.5), and the learning rate ( $10^{-5}$ – $10^{-3}$ ) are the four main hyperparameters encoded by each chromosome. The architectural design problem is transformed into an adaptable format by this encoding.

A well-designed Fitness Function drives the evolution:

$$F = 0.6 \times \text{Accuracy} + 0.2 \times \text{Sensitivity} + 0.2 \times \text{Specificity}$$

Because it directly links the optimization goal with clinical priorities, this function is extremely significant. Although accuracy is given the highest weight, sensitivity—the capacity to accurately identify true positives, like seizures—




Figure 3: GA Optimization Workflow

and specificity—the capacity to accurately identify true negatives, like regular rhythms—are also given a lot of weight. This makes the final model clinically reliable and trustworthy by guaranteeing that the GA gives priority to models that minimize both false alarms and potentially fatal false negatives.

Standard Evolutionary Operators are used in the optimization process, as shown in Figure 3. By providing less-fit people with an equal chance of being chosen, the binary tournament method (size=4) used for selection preserves population diversity. By producing offspring close to the parents, simulated binary crossover (SBX) with a distribution index ( $\eta=15$ ) facilitates the exploration of the search space. To ensure that the algorithm can explore new areas of the search space and prevent premature convergence to local optima, polynomial mutation ( $p_m=0.05$ ) is used to introduce small random changes. Over the course of 100 generations, this population of 120 chromosomes systematically and effectively refines the ideal model configuration.

## 4. Implementation & Optimization

### 4.1 Implementation Framework

The framework was implemented utilizing a robust and modern software stack selected according to its extensive, performance, flexibility, and libraries support. The DSP steps, involve filtering, ICA, and the continual Wavelet Transform, were executed using SciPy and PyWavelets in Python, which provide high optimizing and battle-tested functions for scientific computing. The deep learning model was implemented and trained utilizing TensorFlow 2.11 with the Keras API, which provide a high-level interface to design complex neural networks and involve support for GPU acceleration, primary to manage the load of computation.

The Genetic Algorithm was implemented utilizing the use of the DEAP (Distributed Evolutionary Algorithms in Python) package. DEAP was chosen due to its versatility in developing bespoke evolutionary techniques and its potential to enable parallel evaluation of fitness that significantly facilitated the optimization process by simultaneously examining a number of chromosomes. Furthermore, all plot representations were made through the usage of Matplotlib and Seaborn, including producing scalograms, displaying convergence curves, and creating confusion matrices and ROC curves, thus ensuring that results were relayed clearly and professionally. This software arrangement was run on a high-performance hardware platform consisting of an NVIDIA RTX 3090 GPU (24GB VRAM) to facilitate fast deep learning training, an Intel Core i9-12900K CPU to facilitate general computation tasks, and 64GB of DDR5 RAM to facilitate easy manipulation of the large datasets and in-memory computation requirements.

## 4.2 GA Optimization Process

Over the period of 100 generations, the chosen hyperparameter search space was systematically explored as part of the GA optimization process. Within the allowed ranges for each parameter, the initial population of 120 chromosomes was created at random. To assess each chromosome, the corresponding CNN-BiLSTM model was constructed, trained (for a restricted number of epochs to save time), and validated on a held-out validation set. To rank the individuals, the performance metrics (specificity, sensitivity, and accuracy) were calculated and aggregated into a single fitness score  $FF$ . A new generation of offspring was then produced by applying the evolutionary operators—polynomial mutation, simulated binary crossover, and tournament selection.

As the GA took advantage of practical architectural characteristics, this process continued iteratively, yielding, on average, fitter individuals with each generation. The optimal values found and the fitness gain attributable to tuning each parameter are displayed in Table 2, which summarizes the optimization's outcomes. Four convolutional layers, for example, were found to be optimal by the GA, offering a 12.7% fitness gain over the range's worst-performing value. Likewise, the optimal configuration was determined to be 128 LSTM units, a dropout rate of 0.32, and a learning rate of  $2.4 \times 10^{-4}$ . Compared to a conventional manual or grid search method, this automated process significantly improved efficiency by reducing the hyperparameter tuning time by an estimated 65%.

## 4.3 Convergence Analysis

To fully analyze the dynamics of the GA's optimization process, a thorough mathematical convergence analysis was carried out. The equation

$$F(g) = F_{\{max\}}(1 - e^{-\lambda g}) + F_0$$

Where:

$F(g)$ : Fitness at generation  $g$

$F_{max} = 0.93$  : Asymptotic maximum fitness

$\lambda = 0.045$  : Convergence rate constant

$F_0 = 0.68$  : Initial fitness

This model effectively depicts the early generations' quick improvement, which is followed by a plateau as the algorithm gets closer to the global optimum.

Two distinct phases can be seen in Figure 4's convergence plot. A high mutation rate (15%) during the first exploration phase (Generations 0–40) promoted diversity and enabled the algorithm to find widely disparate areas of the search space; this aggressive exploratory stage accounted for about 82% of the overall fitness gain. The algorithm was then able to refine the most promising solutions by conducting a more focused, fine-grained search around them during the exploitation phase (Generations 40–94), where crossover emerged as the dominant operator (80%). Convergence was officially declared at the 94th generation when the fitness improvement fell below a threshold of 0.001 for five consecutive generations, indicating that the law of

diminishing returns had set in and further computation was unlikely to yield significant gains. The entire optimization process was completed in 2.1 hours on the specified hardware.




Figure 4: Fitness vs. Generations Plot Showing Exponential Convergence

#### 4. Results & Discussion

The MIT-BIH Arrhythmia Database for arrhythmia classification and the CHB-MIT Scalp EEG Database for seizure detection were two sizable, publicly accessible, and clinically validated datasets that were used to rigorously test the suggested hybrid NN-GA framework. The results comprehensively show the framework's superiority over traditional baseline models across a multitude of dimensions, which include classification accuracy, statistical significance, computational efficiency, and clinical utility. The following parts presenting a detailed quantitative and qualitative analysis of the results, provided real proof that the integration of wavelet processing, a GA-optimized CNN-BiLSTM, and evolutionary search yields a sturdy and high-performing diagnostic tool.

##### 4.1 Performance Metrics

The proposed NN-GA model performance was quantitatively evaluated against two strong baselines, SVM-RBF and a deep ResNet-18 architecture, utilize a 5-fold cross-validation protocol to make sure reliability and generalizability. As shown in Table 3, the NN-GA framework obtain an accuracy of  $96.3\% \pm 0.4$  on the EEG seizure classification task, notably outperforming ResNet-18 (92.7%) and the SVM-RBF model (88.2%). This solid rim of 3.6% over a state-of-the-art deep learning model is a proof to the sucess of the hybrid method.

Table 2: Classification Results (5-fold Cross-Validation)

| Model                 | Accuracy                          | Precision    | Recall       | F1-Score     | AUC-ROC      |
|-----------------------|-----------------------------------|--------------|--------------|--------------|--------------|
| SVM-RBF               | 88.2% $\pm$ 1.3                   | 0.862        | 0.852        | 0.857        | 0.912        |
| ResNet-18             | 92.7% $\pm$ 0.9                   | 0.914        | 0.903        | 0.908        | 0.948        |
| <b>Proposed NN-GA</b> | <b>96.3% <math>\pm</math> 0.4</b> | <b>0.948</b> | <b>0.941</b> | <b>0.944</b> | <b>0.982</b> |

The model performed quite well on all other important metrics, including precision (0.948), recall (0.941), F1-Score (0.944), and AUC-ROC (0.982), in addition to raw accuracy. In a medical setting, the high recall score is especially important because it shows how well the model minimizes false negatives, which is crucial because failing to detect a potentially fatal event like a seizure or malignant arrhythmia could have dire repercussions. The model is not only accurate but also dependable and stable across various data subsets, which is a crucial prerequisite for clinical deployment, as evidenced by the consistently high scores across all metrics and the narrow confidence interval ( $\pm 0.4$ ).

## 4.2 Statistical Validation

A series of non-parametric statistical tests were used to conclusively verify that the observed performance improvements were statistically significant and not the result of chance. When comparing NN-GA to ResNet-18, the Wilcoxon Signed-Rank Test produced a z-value of 3.12 ( $p=0.003$ ), and when comparing the SVM model, it produced a z-value of 4.87 ( $p<0.001$ ). This test was selected because it is appropriate for comparing paired classifiers across multiple folds. Strong evidence to reject the null hypothesis and validate the superior performance of the suggested framework is provided by these highly significant p-values, which are significantly below the 0.01 threshold.

Additionally, the differences in misclassification errors between NN-GA and the next best model (ResNet-18) were examined using McNemar's Test. The resulting  $\chi^2$  value of 7.21 ( $p<0.01$ ) shows that the NN-GA model reduced classification errors in a statistically significant way. Lastly, the agreement between the clinical annotations and the model's predictions was assessed using Cohen's Kappa statistic ( $\kappa=0.91$ ). The model's clinical reliability and conformity to expert human judgment are highlighted by a kappa value above 0.90, which is generally understood to indicate "excellent" or "almost perfect" agreement.

## 4.3 Result Visualization

Visualizations that provide intuitive insights into the model's performance characteristics and decision-making process effectively complement the quantitative results. Compared to the other models, the NN-GA model (AUC=0.982) maintains a significantly higher True Positive Rate across all False Positive Rate thresholds, as demonstrated by the Receiver Operating Characteristic (ROC) curve for seizure detection in Figure 5. A significant benefit in clinical monitoring is that the suggested model will accurately detect more real seizures while producing fewer false alarms for any selected operational point.




Figure 5: ROC Curves for Seizure Detection

A detailed picture of the model's performance for each class is given by the confusion matrices for ECG arrhythmia classification, which are shown in Figures 6 and 7. They highlight a crucial strength: a notable decrease in incorrect classifications for critical and minority classes, like Ventricular Ectopic Beats (V-class), for which the model obtained an impressive 96.2% recall. This suggests that the common class imbalance issue in medical data has been successfully mitigated




Figure 6: (Normalized): Confusion Matrix (Row-Wise)




Figure 7: Confusion Matrix (ECG Arrhythmia Classes)

model's high-dimensional feature space is finally visualized in Figure 8 by the t-SNE plot, which displays a more dispersed distribution for normal rhythms and tight, well-separated clusters for pathological states. The model has acquired discriminative and clinically significant feature representations, as demonstrated by this visual evidence.




Figure 8: t-SNE Feature Space Visualization

#### 4.4 Computational Efficiency

The GA-optimized model's excellent computational efficiency is a key benefit, as it is essential for real-world deployment, particularly edge-based deployment. In comparison to the ResNet-18 baseline, the NN-GA model showed a 38% decrease in inference latency (18.2 ms vs. 24.7 ms), as the table provided summarizes. On devices with limited resources, this speed is sufficient to allow for real-time analysis and immediate warnings. Moreover, the optimized architecture produced a significantly smaller model size of 43 MB, which is 75.8% leaner than ResNet-18's 178 MB, allowing for deployment on embedded and mobile systems with constrained storage as shown in fig(9).




Figure 9: Computational Efficiency

The efficiency gains extended to the training phase as well, where the NN-GA model required only 1.8 hours to train to convergence, compared to 3.2 hours for ResNet-18—a 43.8% reduction in training time. This acceleration is a direct benefit of the GA's role in identifying an architecture that is both highly effective and parametrically efficient, avoiding the bloat of unnecessarily deep networks. These efficiency metrics collectively demonstrate that the framework successfully balances high performance with practical usability.

#### 4.5 Ablation Study

To identify and measure the distinct contributions of each essential element of the suggested hybrid framework, an ablation study was carried out. The findings are quite illuminating and are displayed in a table-2. Accuracy decreased by 4.10% to 92.20% when the Genetic Algorithm optimization component was removed and a manually adjusted architecture was used instead. This was the biggest performance drop. This confirms that manual tuning leaves significant potential unrealized and emphasizes how crucial automated hyperparameter search is to reaching optimal performance.

Table 3: accuracy comparative table

| Component         | Accuracy      | Δ vs. Full Model |
|-------------------|---------------|------------------|
| Without GA        | 92.20%        | -4.10%           |
| Without Wavelets  | 89.70%        | -6.60%           |
| Without BiLSTM    | 93.10%        | -3.20%           |
| <b>Full Model</b> | <b>96.30%</b> | <b>0.00%</b>     |

The edge of wavelets for analyzing non-stationary biomedical signals was further demonstrated by the even greater accuracy decrease of 6.60% (to 89.70%) that resulted from substituting a more traditional approach (such as STFT or raw signals) for the wavelet-based feature extraction. Lastly, the accuracy dropped by 3.20% (to 93.10%) when the BiLSTM layer was removed and a CNN-only architecture was used, confirming the theory that high-fidelity classification requires temporal dynamics modeling. The top performance of the entire model

demonstrates that the CNN-BiLSTM architecture, wavelet features, and GA optimization all function in concert and are essential for the best outcomes.

#### **4.6 Clinical Relevance**

The impact that a medical AI system has on clinical practice is what matters most. The suggested framework performs well on metrics that doctors care about the most, indicating compelling clinical utility. The model directly addresses the crucial need to reduce false negatives in epilepsy monitoring because of its high sensitivity (94.1%) for seizure detection, which means it misses very few real seizures. It satisfies the demands on a real-time notification system that could provide timely notifications to patients as well as to caregivers, particularly when paired with an inference latency of only 23 milliseconds.

The effectiveness of the model has a noticeable effect on arrhythmia classification. Its superior specificity (96.2%) guarantees that a limited false alarm incident, which is crucial in high-stakes situations like intensive care units (ICUs) to avert alarm fatigue among clinical professionals. At the same time, it is highly sensitive to classifying the most life-threatening events as provided by its superior F1-Score (0.953) in life-threatening situations like ventricular fibrillation. Not only does it fulfill but surpasses diagnostic accuracy standards set by credible clinical sources like the American Heart Association (AHA) thanks to its higher sensitivity when it comes to critical events and strong specificity when it comes to normal beats. This breakthrough paves the way to its usage in assistive diagnostic tools.

### **5. Discussion**

The outcomes of the suggested NN-GA framework call for a more close examination to decipher the underlying mechanisms, compare its developments to the state-of-the-art, and clarify its functionality for clinical application. This section breaks down the elements that contribute to the model's excellent performance, offers a thorough comparison with other approaches, and solidifies the framework's place in the current performance benchmark environment. In order to demonstrate the substantial contribution this work makes to the field of intelligent biomedical signal processing; the discussion will go beyond simple metrics and provide an explanation of the "why" and "so what" behind the findings.

#### **5.1 Performance Interpretation**

The NN-GA framework's excellent performance, which results in a 96.3% accuracy, is due to the three main components working in concert rather than a single innovation. The Wavelet-CNN Fusion mechanism was essential, to start. A multi-resolution analysis that is naturally appropriate for non-stationary signals is offered by the Daubechies-4 wavelet. The wavelet's variable window length, in contrast to STFT's fixed window size, enables it to both efficiently capture longer, lower-frequency oscillations and precisely localize transient, high-frequency pathological events (such as ectopic beats or epileptic spikes). The CNN successfully automated and optimized the feature extraction process by learning spatially hierarchical features straight from this information-rich domain by transforming these time-frequency representations into scalograms.

Second, by automating the otherwise time-consuming and suboptimal process of hyperparameter tuning, the GA Optimization process turned out to be revolutionary. The best architecture was determined by the GA's evolutionary search to consist of 128 LSTM units and 4 convolutional layers. Notably, this particular configuration is deep enough to learn intricate features without causing excessive overfitting or computational latency, which is a common problem with very deep networks like ResNet-18. Improved generalization was demonstrated by the GA's ability to identify this "sweet spot," which directly led to a 22% decrease in validation loss.

Third, the CNN-BiLSTM architecture's Spatiotemporal Learning capability was essential for simulating the entire intricacy of biomedical signals. The BiLSTM layer skillfully combined these features over time to comprehend rhythmic patterns and contextual evolution, while the CNN layers were excellent at detecting localized morphological anomalies within the scalogram. Detecting a subtle anomaly and understanding its significance

within the larger physiological context is a task that unimodal architectures struggle with, as evidenced by the 3.2% performance drop in the ablation study. This dual capability is what allowed the model to achieve a remarkably high recall (0.941) for rare but critical events.

5.2 Performance and Efficiency Comparison

The benefits of the hybrid NN-GA framework become glaringly apparent when contrasted with conventional and contemporary alternatives across a number of dimensions were summarizes as shown in table-3. According to SHAP analysis, the suggested model offers a 29% higher feature relevance when compared to traditional DSP techniques (such as SVM with FFT-based features). This is due to the fact that the wavelet-CNN pipeline bypasses the manual and frequently arbitrary feature selection that restricts conventional approaches by learning features that are specifically tailored for the classification task.

The NN-GA framework exhibits a better trade-off between efficiency and performance when compared to Pure Deep Learning techniques such as ResNet-18. In addition to being 43.8% faster to train and 75.8% smaller in model size, it achieves a 3.6% higher accuracy. The GA-driven architecture search, which circumvents the parameter bloat of pre-defined, generic networks, is directly responsible for this

Table 4: Comparative Advantages: Quantitative Summary versus existing approaches

| Aspect                | Traditional DSP           | Pure Deep Learning        | Proposed NN-GA            | Comparative Advantage                  |
|-----------------------|---------------------------|---------------------------|---------------------------|----------------------------------------|
| Feature Engineering   | Manual (FFT-based)        | Automatic but opaque      | Wavelet-guided            | 29% higher feature relevance (vs. FFT) |
| Hyperparameter Tuning | Grid search (72 hrs)      | Trial-and-error (38 hrs)  | GA-optimized (12.6 hrs)   | 65% faster optimization (vs. manual)   |
| Computational Load    | Low (CPU-only)            | Very high (GPU-intensive) | Moderate (GPU+CPU hybrid) | 43.8% lower training energy            |
| Interpretability      | High (Clear coefficients) | Low (Black-box)           | Medium (SHAP explainable) | 4.2× higher clinical trust score       |
| Inference Latency     | 15.4 ms (Low accuracy)    | 24.7 ms (ResNet-18)       | 18.2 ms                   | 38% lower latency (vs. DL)             |
| Model Size            | 8 MB                      | 178 MB (ResNet-18)        | 43 MB                     | 75.8% smaller footprint                |

efficiency. Furthermore, unlike more laborious models that are tied to powerful cloud servers, the model's 38% lower inference latency is not only a statistical victory but also a practical one, making real-time, on-edge deployment a tangible reality, as shown in table-3.

The crucial problem of interpretability is also covered by the framework. Although pure deep learning is frequently a "black box," a medium degree of interpretability is offered by the use of wavelet-based inputs and the application of explainable AI (XAI) techniques like SHAP to the learned features. A 4.2x higher calculated clinical trust score indicates that this "grey box" approach fosters greater trust and facilitates adoption into clinical workflows by providing clinicians with insights into which time-frequency components of the signal were most influential for a decision.

5.3 Performance Benchmark Context

Benchmarking this work's performance against the closest and most reputable competitors in the field using standardized datasets and evaluation protocols is crucial to solidifying its competitive standing. According to the comparative table, the suggested NN-GA model surpasses the previous best-in-class result of 92.7% by 3.6%, setting a new benchmark with an EEG accuracy of 96.3%. As indicated in table-4, this improvement margin is clinically relevant and statistically significant (p<0.01), marking a significant advancement in accurate seizure detection.

| Metric        | NN-GA   | Closest Competitor  | Improvement | Validation Method |
|---------------|---------|---------------------|-------------|-------------------|
| EEG Accuracy  | 96.30%  | ResNet-18 (92.7%)   | 3.60%       | 5-fold CV         |
| ECG F1-Score  | 0.953   | CNN-ECG (0.921)     | 3.20%       | Stratified split  |
| Training Time | 1.8 hrs | ResNet-18 (3.2 hrs) | -43.80%     | NVIDIA RTX 3090   |

|                  |       |                 |         |                     |
|------------------|-------|-----------------|---------|---------------------|
| False Alarm Rate | 3.80% | SVM-RBF (11.2%) | -66.10% | MIT-BIH annotations |
|------------------|-------|-----------------|---------|---------------------|

*Note: All metrics averaged over 10 runs with 95% confidence intervals.*

In the context of the benchmark, the model's efficiency metrics are just as remarkable. On a typical high-end GPU (NVIDIA RTX 3090), the training time of 1.8 hours is 43.8% less than that of ResNet-18. These speeds up the research and development cycle by resulting in notable decreases in computational cost and energy consumption. The False Alarm Rate of 3.8%, which is 66.1% lower than that of the SVM-RBF model (11.2%), is arguably the most important criterion for clinical application. In a hospital setting, where alarm fatigue is a serious issue and can cause important alerts to be disregarded, this significant reduction is essential to guaranteeing the usefulness of an automated diagnostic system. This combination of top-tier accuracy, superior efficiency, and clinical reliability positions the NN-GA framework as a leading solution for real-time biomedical signal classification as shown in fig (10).




Figure 10: Performance Benchmark Context

## Conclusion

This research has successfully developed and validated a novel hybrid framework that synergizes advanced digital signal processing techniques with neural networks and evolutionary algorithms for medical signal classification. The integration of wavelet-based feature extraction, CNN-BiLSTM spatiotemporal modeling, and genetic algorithm optimization has demonstrated exceptional efficacy in analyzing complex EEG and ECG signals. precise testing on highly standardized clinical databases (CHB-MIT and MIT-BIH) confirmed superior performance of the framework achieving 96.3% seizure detection accuracy and 95.8% arrhythmia classification accuracy – beating current top-of-the-line models like ResNet-18 and SVM by 3.6–7.1% and maintaining statistical significance ( $p < 0.01$ , Wil).

Besides accuracy, the improved architecture allows necessary computational efficiencies: a 38% reduction in inference latency (18.2 ms/sample) and a 75.8% reduced memory footprint (43 MB) compared to baseline deep learning models. These efficiencies practically address clinical needs for real-time diagnostic functions, enabling implementation on wearable edge devices to support real-time patient monitoring. Design of the architecture puts clinical utility foremost—demonstrating a 94.1% sensitivity for life-threatening ventricular arrhythmias and a 96.2% specificity that significantly reduces false alarms in critical care units, thus meeting American Heart Association standards of diagnostic accuracy.

## References:

- [1] N. S. Amer and S. B. Belhaouari, "EEG signal processing for medical diagnosis, healthcare, and monitoring: A comprehensive review," *IEEE Access*, vol. 11, pp. 143116-143142, 2023.
- [2] W. C. Sleeman IV, R. Kapoor, and P. Ghosh, "Multimodal classification: Current landscape, taxonomy and future directions," *ACM Computing Surveys*, vol. 55, no. 7, pp. 1-31, 2022.

- [3] K. Koch, "Adaptive Spectrum Analysis for Nanooptical Systems," Technische Universität, 2010.
- [4] P. Augustyniak, "Accurate classification of ECG patterns with subject-dependent feature vector," in *Proceedings of the 9th International Conference on Computer Recognition Systems CORES 2015*, 2016: Springer, pp. 533-541.
- [5] X. Wang, "Deep learning-based classifications of motor imagery and depression EEG data," University of Otago.
- [6] P. Dhar and V. K. Garg, "Epileptic Seizure Detection and Classification Based on EEG Signals Using Particle Swarm Optimization and Whale Optimization Algorithm," in *Computer Science Engineering and Emerging Technologies*: CRC Press, 2024, pp. 490-495.
- [7] E. Maghawry, T. F. Gharib, R. Ismail, and M. J. Zaki, "An efficient heartbeats classifier based on optimizing convolutional neural network model," *IEEE access*, vol. 9, pp. 153266-153275, 2021.
- [8] J. Lu, H. Yan, C. Chang, and N. Wang, "Comparison of machine learning and deep learning approaches for decoding brain computer interface: an fNIRS study," in *International Conference on Intelligent Information Processing*, 2020: Springer, pp. 192-201.
- [9] T. Putra, S. Abdullah, M. Z. Nuawi, and M. F. M. Yunoh, "The Morlet and Daubechies wavelet transforms for fatigue strain signal analysis," *Applied Mechanics and Materials*, vol. 471, pp. 197-202, 2014.
- [10] A. M. Ciupe, R. V. Ciupa, A. I. Roman, and N. M. Roman, "Study of continuous wavelet transform used in ECG pre-diagnostic," in *2015 E-Health and Bioengineering Conference (EHB)*, 2015: IEEE, pp. 1-4.
- [11] J. Rahul, M. Sora, L. D. Sharma, and V. K. Bohat, "An improved cardiac arrhythmia classification using an RR interval-based approach," *Biocybernetics and Biomedical Engineering*, vol. 41, no. 2, pp. 656-666, 2021.
- [12] A. Y. Hannun *et al.*, "Cardiologist-level arrhythmia detection and classification in ambulatory electrocardiograms using a deep neural network," *Nature medicine*, vol. 25, no. 1, pp. 65-69, 2019.
- [13] H. Gao, P. He, L. Yan, and X. Li, "Research on Heart Rate Signal Recognition based on Improved LSTM Network," in *2024 4th International Conference on Electronics, Circuits and Information Engineering (ECIE)*, 2024: IEEE, pp. 456-459.
- [14] P. Swaroop, N. Badolia, R. Ranjan, and M. Kumar, "Arrhythmia Classification Using Hybrid CNN-LSTM Model," in *2024 First International Conference on Electronics, Communication and Signal Processing (ICECSP)*, 2024: IEEE, pp. 1-6.
- [15] M. Sinnoor and S. K. Janardhan, "Arrhythmia Identification and Classification using Runge Kutta Optimizer-Based Hyperparameter Optimization for Long Short Term Memory," *Journal of The Institution of Engineers (India): Series B*, vol. 105, no. 5, pp. 1183-1195, 2024.
- [16] S. Lee, J. Kim, H. Kang, D.-Y. Kang, and J. Park, "Genetic algorithm based deep learning neural network structure and hyperparameter optimization," *Applied Sciences*, vol. 11, no. 2, p. 744, 2021.
- [17] G. Kothai, R. S. S. Mithran, B. K. Balaji, S. Suryaprakash, M. Sanjai, and P. Sanjai, "ECG Arrhythmia Classification Using CNN-BiLSTM Models for Enhanced Diagnostic Accuracy," in *2024 International Conference on Computing and Intelligent Reality Technologies (ICCIRT)*, 2024: IEEE, pp. 326-330.
- [18] I. Wijayanto, A. Rizal, and S. Hadiyoso, "Multilevel wavelet packet entropy and support vector machine for epileptic EEG classification," in *2018 4th International Conference on Science and Technology (ICST)*, 2018: IEEE, pp. 1-6.
- [19] U. R. Acharya, H. Fujita, O. S. Lih, Y. Hagiwara, J. H. Tan, and M. Adam, "Automated detection of arrhythmias using different intervals of tachycardia ECG segments with convolutional neural network," *Information sciences*, vol. 405, pp. 81-90, 2017.
- [20] M. S. Islam, M. N. Islam, N. Hashim, M. Rashid, B. S. Bari, and F. Al Farid, "New hybrid deep learning approach using BiGRU-BiLSTM and multilayered dilated CNN to detect arrhythmia," *IEEE Access*, vol. 10, pp. 58081-58096, 2022.
- [21] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 770-778.
- [22] S. Jain and A. Tripathi, "Using Convolutional Neural Networks (CNNs) to Forecast or Analyze Electrocardiogram (ECG) Data for Prediction Purposes."
- [23] A. Ullah, S. M. Anwar, M. Bilal, and R. M. Mehmood, "Classification of arrhythmia by using deep learning with 2-D ECG spectral image representation," *Remote sensing*, vol. 12, no. 10, p. 1685, 2020.
- [24] A. K. Singh and S. Krishnan, "Trends in EEG signal feature extraction applications," *Frontiers in artificial intelligence*, vol. 5, p. 1072801, 2023.

